

Dimplex Wall Controller (DWC)



Technical Details

Controls:	Digitally controlled, electronic thermostat accurate to ($\pm 0.2^{\circ}\text{C}$) with a setpoint range of 7 to 26°C. Continuous heat modes: Manual Additional modes: Boost
Controller UI:	Portrait segmented display with 4 touch buttons <ul style="list-style-type: none"> Boost - to provide a temporary increase in heating outside the timed heating period Down / Up - to change temperature up or down Enter - to confirm and select any changes
Controller Functions: (*Available via the ConfigR App.)	Bluetooth signalling to the panel heater, manual mode and real time clock (RTC) display *Programming : 7-day /4-daily time periods / Runback / Lock /Adaptive start / Lock/ Open window detection
Display:	Non-illuminated LCD mapped screen with auto-standby energy saving sleep mode
Construction Colour/Finish:	White plastic moulded case and backplate
Installation:	Wall mounted controller requires 2 x small screws with appropriate wall material fixings
IP Rating:	IP20
Battery Requirement:	2 x AA batteries are supplied with an estimated life of ? months in daily use. (Please note there is no battery level indicator or battery back up so the controller should be regularly checked and maintained).

Approvals and Guarantee

Approvals:	RED, RoHS, REACH, WEEE
Guarantee:	2 Years
Country of Origin:	United Kingdom
Manufacturer:	Glen Dimplex Heating & Ventilation (Glen Dimplex UK Ltd.)


Product Description

An ideal commercial heating solution for hotel rooms and student accommodation, the DWC is a wall mounted controller which enables manager-defined, tamperproof control functions of a PLXE NC panel heater by the room occupier.

Key Features

- Each DWC unit communicates with a single paired PLXE NC panel heater via Bluetooth Low Energy, allowing restricted programmed heater commands.
- User interface for (No Controls) panel heaters that are without on board controls.
- Quick set-up using the ConfigR App's step-by-step wizard enables full configuration at installation.
- Diagnostics, over the air, and firmware updates can be carried out between the Dimplex Wall Controller to the PLXE NC using the ConfigR App.

Dimensions



Model/ Item No. (EAN Code 5011139065698)	065698	DWC
Width A (mm)	100	
Height B (mm)	100	
Depth C (mm)	27	
Weight without batteries (kg)	0.115	
Weight with batteries (kg)	0.16	

Packaging Details

Pack width (mm)	118
Pack Height (mm)	118
Pack Depth (mm)	32
Individual Packed Weight (kg)	0.2