

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

73R23BC-B

Hartland | HARTLAND RANGE | Rocker Switches

Primary Range Hartland Insert Type 3 gang 10AX 2 Way Rocker Insert Colour Bright Chrome/Black EANI3 Barcode 501750.3236237 Commodity Code 85363010 Luckins TS1 386551889 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 122 CR Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency SOH2 IP Rating 1P2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x4mm² Multi-strand Earth Terminal Capacity 9 1x4mm² 1	Item Image	Wiring	Dimensions
Insert Type		Live to Load Live in Large	HARTLAND R23 2 Way Rocker
Insert Colour Bright Chrome/Black EAN13 Barcode 5017503236237 Commodity Code 85363010 Luckins TSI 385551889 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 122 GR Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1	Primary Range	Hartland	
EAN13 Barcode 5017503236237 Commodity Code 85363010 Luckins TSI 385551889 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 122 GR Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 5xlmm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x4mm² Multi-strand Earth Terminal Capacity 5 1x4mm² Multi-strand Earth Terminal Capacity 5 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 6 1x6mm² Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only		3 gang 10AX 2 Way Rocker	
Commodity Code 85363010 Luckins TSI 385551889 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 122 GR Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Insert Colour		
Luckins TSI 385551889 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 122 GR Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	EAN13 Barcode	5017503236237	
Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 122 GR Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 3 1x4.5mm² Earth Terminal Capacity 3 1x4.5mm² Earth Terminal Capacity 3 1x4.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Commodity Code	85363010	
Weight 122 GR Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Luckins TSI	385551889	
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 Sxlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x4mm² 5xlmm² Earth Terminal Capacity 9 1x4mm² 5xlmm² Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 9 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only	Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm	
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 6 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Weight	122 GR	
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Switched Poles	Single	
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 2 4xl.5mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 2 4xl.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Current Rating	10AX	
Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 Ix2.5mm² Terminal Capacity 4 Ix4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 Earth Terminal Capacity 4 Ix4mm² Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Ix4mm² Multi-strand Earth Terminal Capacity 5 Ix6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Voltage	220/250V AC	
IP Rating IP2XD Contact Cap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Maximum Load	10 Amp inductive	
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 9 Terminal C	Mains Frequency	50Hz	
Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	IP Rating		
Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Contact Gap Minimum		
Terminal Capacity 3	Terminal Capacity 1		
Terminal Capacity 4 Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Ix4mm² Multi-strand Earth Terminal Capacity 5 Ix6mm² Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only			
Terminal Capacity 5	Terminal Capacity 3	1x2.5mm²	
Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only		3x2.5mm ²	
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Recommended Location Internal Use Only			
, , , , , , , , , , , , , , , , , , ,			
Maximum Installation Altitude 2000m			
	Maximum Installation Altitude	2000m	



Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

73R23BC-B Hartland | HARTLAND RANGE | Rocker Switches Standard/Approval BS EN 60669-1 It is the policy of the company to All products listed conform to current All accessories are manufactured improve products as part of our British or European standard and the under an accredited BS EN ISO 9001: development programme. Therefore, product information is correct at the 2015 Quality Management System. we reserve the right to alter designs time of going to press. and dimensions without prior notice. Illustrations and diagrams are Due to manufacturing processes we reproduced within the limitations of cannot guarantee an exact colour Correct as at 18 August 2021 07:56 AM reproduction and printing process and match and shadings of of certain E&OE are not binding. finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB

Registered in London No. 941624 VAT Registration No. 222 6607 84

73R23BC-B - Hartland Bright Steel 3 gang 10AX 2 Way Rocker Bright Chrome/Black